

TECHNICAL SPECIFICATION

(from series 2018 on)



BeachTech 2000

Data sheet

Cleaning method		BechTech 2000
	Patented	Raking-screening-mixed technique
Tractor requirements		
	Recommended power output	55 kW (70 hp) **
	4-wheel-drive	
	Differential lock	
	2-point hitch cat. 1 or 2	
	PTO shaft	6 spline, 1 3/8"
	Power take-off AR NORM	540 rpm (1000 rpm)
	2 double-acting circuits of the additional tractor hydraulics in standard operation	
	Power supply	12 V
Dimensions		
Length		5,430 mm
Width	Small tires	2,300 mm
	Wide tires	2,610 mm
	With finisher	2,500 mm
Height	Working width	1,850 mm
	Overall vehicle height	2,100 mm
	Unloading hopper max.	2,600 mm
Tires		
	Small	360/70-16
	Wide, low pressure	520/50-17
Weight		
	Net weight	1,800 kg
	Technically permissible total weight	2,800 kg *
Tank capacity		
	Hydraulic oil	30 l
Performance		
	Area coverage up to	22,200 m ² /h **
Working depth		
	up to	30 cm **
Screen surface		
	Screening belt	+/- 4 m ²
Capacity		
	Collection hopper	1.5 m ³
Speed		
	Operating speed max.	12 km/h **
	Road traffic max.	25 km/h // 40 km/h *

The possibility of changes to the product after the editorial closing date for this publication cannot be ruled out.

* Road transport according to local regulation

** Depending on the soil conditions

Dealer stamp

BeachTech

Tel.: +49 7392 900 - 461
 Email: info@beach-tech.com
 www.beach-tech.com